

Technical Parameter

HighMate V40 Specifications

Efficiency	35-55 m ² /h	Dimension	810*1154*552 mm
Weight	91 kg	Cleaning Width	300 mm
Pressure	3000 bar	Protection Level	IP65
FlowRate	18-52 L/min	Minimum Curvature	8 m

HighMate V45 Specifications

Efficiency	45-65 m ² /h	Dimension	825*1200*525 mm
Weight	97 kg	Cleaning Width	310 mm
Pressure	3000 bar	Protection Level	IP65
FlowRate	18-52 L/min	Minimum Curvature	4 m

HighMate V40E Specifications

Dimension (LxWxH)	1105x575x526 mm/1181x517x477 mm		
Weight	86/89 kg	Power	1.2 kW/1.5 kW
Cleaning Width	310/400 mm	Power Supply	220VAC,48V DC
Production Rate	40-60 m ² /h (WJ2.0/WJ2.5) (Efficiency varies with parameters such as operators 'proficiency, coating type,and water pressure)		
Remote Control Range	80 m	Working Temperature	0-55°C
Protection Grade	IP 68	No.of Nozzles	16/20
Max Flow Rate	52 L/min	Max Pressure	3000 bar

HighMate Ex V10 Specifications

Efficiency	35-55 m ² /h	Dimension	740*1018*510 mm
Weight	100 kg	Cleaning Width	300 mm
Pressure	3000 bar	Protection Level	IP65
FlowRate	30-45 L/min	Minimum Load	100 kg