

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D2-1000-P5	2	5kg	Weight	Diameter	Position	Rotation	350pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	4kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			55kg	1000mm	0.05mm	—				34°	75°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D2-1000-P15	2	15kg	Weight	Diameter	Position	Rotation	300pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			60kg	1000mm	0.05mm	—				25°	77°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D2-1300-P15	2	15kg	Weight	Diameter	Position	Rotation	300pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			60kg	1300mm	0.05mm	—				25°	77°						