

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
D3W-1100-P5	3	5kg	Weight	Diameter	Position	Rotation	600pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			88kg	1100mm	0.05mm	—				32.5°	68.5°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
D3W-1100-P15	3	15kg	Weight	Diameter	Position	Rotation	500pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			115kg	1100mm	0.05mm	—				23.5°	70°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
D3W-1300-P5	3	5kg	Weight	Diameter	Position	Rotation	580pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			90kg	1300mm	0.05mm	—				31.5°	74°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3W-1300-P15	3	15kg	Weight	Diameter	Position	Rotation	500pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			120kg	1300mm	0.05mm	—				29.9°	63.6°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3W-1600-P3	3	3kg	Weight	Diameter	Position	Rotation	550pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			93kg	1600mm	0.05mm	—				22°	76°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3W-1600-P15	3	15kg	Weight	Diameter	Position	Rotation	480pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			133kg	1600mm	0.05mm	—				23°	71.5°						