

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3WB-450-P3	3	3kg	Weight	Diameter	Position	Rotation	550pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	3KVA	1.2kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			38.7kg	450mm	0.05mm	—				42.5°	69.8°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3WB-600-P3	3	3kg	Weight	Diameter	Position	Rotation	550pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	3KVA	2.3kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			38.7kg	600mm	0.05mm	—				42.5°	69.8°						