

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3WZ-800-P1	3	1kg	Weight	Diameter	Position	Rotation	600pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	6KVA	2.25kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55/IP67
			82kg	800mm	0.05mm	—				30°	62°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3WZ-800-P3	3	3kg	Weight	Diameter	Position	Rotation	600pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	6KVA	2.25kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55/IP67
			79.5kg	800mm	0.05mm	—				42.5°	65.8°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3WZ-1100-P1	3	1kg	Weight	Diameter	Position	Rotation	600pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55/IP67
			89kg	1100mm	0.05mm	—				28°	71°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
D3WZ-1100-P5	3	5kg	Weight	Diameter	Position	Rotation	600pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55/IP67
			82kg	1100mm	0.05mm	—				32.5°	68.5°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
D3WZ-1300-P5	3	5kg	Weight	Diameter	Position	Rotation	580pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			85kg	1300mm	0.05mm	—				31.5°	74°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
D3WZ-1600-P3	3	3kg	Weight	Diameter	Position	Rotation	550pp/min	—	—	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			91kg	1600mm	0.05mm	—				22°	76°						