

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
D3PB-600-P3	3+1	3kg	Weight	Diameter	Position	Rotation	500pp/min	±360°	31×10 ⁻⁷ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	3KVA	2.4kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			66kg	600mm	0.05mm	0.1°				36.5°	65.5°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
D3PB-800-P3	3+1	3kg	Weight	Diameter	Position	Rotation	500pp/min	±360°	31×10 ⁻⁷ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	6KVA	2.4kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			83.8kg	800mm	0.05mm	0.1°				47.3°	60.2°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
D3PB-1100-P3	3+1	3kg	Weight	Diameter	Position	Rotation	500pp/min	±360°	31×10 ⁻⁷ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	2.4kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			85.5kg	1100mm	0.05mm	0.1°				39.2°	77.1°						