

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3PZ-800-P1	3+1	1kg	Weight	Diameter	Position	Rotation	600pp/min	±360°	31×10 ⁻ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	6KVA	2.35kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55/ IP67
			86kg	800mm	0.05mm	0.1°				24.6°	78.5°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3PZ-800-P3	3+1	3kg	Weight	Diameter	Position	Rotation	600pp/min	±360°	31×10 ⁻ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	6KVA	2.35kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55/ IP67
			83kg	800mm	0.05mm	0.1°				30.2°	63.6°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3PZ-1100-P1	3+1	1kg	Weight	Diameter	Position	Rotation	600pp/min	±360°	80×10 ⁻ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6.1kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55/ IP67
			93kg	1100mm	0.05mm	0.1°				24.5°	73.5°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
D3PZ-1100-P3	3+1	3kg	Weight	Diameter	Position	Rotation	600pp/min	±360°	31×10 ⁻ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6.1kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55/ IP67
			90.5kg	1100mm	0.05mm	0.1°				24.5°	73.5°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
D3PZ-1300-P3	3+1	3kg	Weight	Diameter	Position	Rotation	540pp/min	±360°	80×10 ⁻ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6.1kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			93.5kg	1300mm	0.05mm	0.1°				24.6°	78.5°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
D3PZ-1600-P3	3+1	3kg	Weight	Diameter	Position	Rotation	500pp/min	±360°	80×10 ⁻ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6.1kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			99.8kg	1600mm	0.05mm	0.1°				28°	73°						