

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3PM-1100-P3	3+1	3kg	Weight	Diameter	Position	Rotation	500pp/min	±360°	31×10 ⁻ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6.1kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			85kg	1100mm	0.05mm	0.05°				32.5°	68.5°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3PM-1100-P15	3+1	15kg	Weight	Diameter	Position	Rotation	350pp/min	±360°	0.224kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6.2kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			113kg	1100mm	0.05mm	0.025°				23.5°	70°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3PM-1300-P3	3+1	3kg	Weight	Diameter	Position	Rotation	450pp/min	±360°	31×10 ⁻ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6.1kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			86.5kg	1300mm	0.05mm	0.05°				31.5°	74°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
D3PM-1600-P3	3+1	3kg	Weight	Diameter	Position	Rotation	400pp/min	±360°	31×10 ⁻⁷ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6.1kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			79.7kg	1600mm	0.05mm	0.05°				22°	76°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
D3PM-1600-P15	3+1	15kg	Weight	Diameter	Position	Rotation	300pp/min	±360°	0.224kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6.2kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			131kg	1600mm	0.05mm	0.025°				23°	71.5°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
D3PM-1800-P15	3+1	15kg	Weight	Diameter	Position	Rotation	260pp/min	±360°	0.224kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6.2kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			134kg	1800mm	0.05mm	0.025°				23°	71.5°						