

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3PMZ-800-P3	3+1	3kg	Weight	Diameter	Position	Rotation	540pp/min	±360°	31×10 ⁻⁷ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	6KVA	2.35kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55/ IP67
			75kg	800mm	0.05mm	0.05°				42.5°	65.8°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3PMZ-1100-P3	3+1	3kg	Weight	Diameter	Position	Rotation	540pp/min	±360°	31×10 ⁻⁷ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6.1kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55/ IP67
			85kg	1100mm	0.05mm	0.05°				32.5°	68.5°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3PMZ-1300-P3	3+1	3kg	Weight	Diameter	Position	Rotation	450pp/min	±360°	31×10 ⁻⁷ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6.1kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			87.5kg	1300mm	0.05mm	0.05°				31.5°	74°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3PMZ-1400-P3	3+1	3kg	Weight	Diameter	Position	Rotation	430pp/min	±360°	31×10 ⁻⁷ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6.1kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			89.5kg	1400mm	0.05mm	0.05°				22°	76°						

Type	Axes	Pay-load	Manipulator		Repeatability		Maximum exercise frequency	Rotation range	Allowable maximum moment of inertia	Angle range of actuated arm		Power supply	Power capacity	Rated power	Storage temperature	Work environment	Protection
			Weight	Diameter	Position	Rotation				Up	Down						
D3PMZ-1600-P3	3+1	3kg	Weight	Diameter	Position	Rotation	400pp/min	±360°	31×10 ⁻⁷ kg·m ²	Up	Down	Three-phase 380VAC -10%~+10% 49~61HZ	10KVA	6.1kw	-10°C~70°C	-10°C~50°C , RH≤80%	IP55
			92.7kg	1600mm	0.05mm	0.05°				22°	76°						